



# Afiscooter M

A powerful electric vehicle designed for diverse service and maintenance purposes. With its impressive carrying capacity and maneuvering capabilities, the Afiscooter M is your ultimate companion.

Super strong vehicle with an advanced ergonomic design to handle loads of up to 250 kg / 551 lb.



- ✓ Offers new benefits for estate managers, hospital and school maintenance, warehouse operatives etc.
- ✓ Fully adjustable comfortable seat with a supportive armrests.
- ✓ Powerful, long-lasting, energy efficient LED headlights providing a wider range of view.
- ✓ Easy tiller adjustment for any driver.
- ✓ Fully electric- provides a silent, environmentally friendly and highly efficient maintenance vehicle.

## Features

- ▶ Extremely large loading surface, long travel range and superb traction.
- ▶ Easy steering and a smooth driving experience in a variety of environments including: service elevators, warehouses and narrow passages.
- ▶ Highly efficient suspension system and shock absorbers.
- ▶ Comfort ride on all terrain throughout full working day

**Afikim Electric Vehicles** is a leader in developing and manufacturing advanced, electrically-powered mobility scooters, since 1987. Afiscooters' product line designed with reliability and driver safety in mind first and foremost, alongside beautiful and thoughtful design. Afikim Electric Vehicles' worldwide distribution network offers local technical support and meets European ISO 9001, CE certifications, as well as US safety standards with FDA approval.







## Advantages



Bright, easy to read LCD display control panel indicates speed, driving length, working hours' counter, battery status, lighting and signing.



Upgrade options: Designed sun/rain canopy for working smoothly in all weather conditions. Top quality rain cover.



Option of Choice Short or Extended Loading Surface 25cm/9.8inch walls and a drop-down tailgate.

## Specifications

		Afiscooter-M - Single		Afiscooter-M - Dual seat	
<b>Overall length</b>		92"	234 cm	92"	234 cm
	Loading surface short	29X34"	74 X 88 cm	29X34"	74 X 88 cm
	Loading surface long	40X34"	103.8 X 88 cm	40X34"	103.8 X 88 cm
<b>Overall width</b>		35"	88 cm	38"	96 cm
<b>Overall height</b>	Without canopy	50"	128 cm	50"	128 cm
	With canopy	66"	167 cm	66"	167 cm
<b>Ground clearance</b>		5"	12.5 cm	5"	12.5 cm
<b>Rear Wheel Track</b>	Inner	20"	50 cm	20"	50 cm
	Outer	35"	88 cm	35"	88 cm
<b>Wheel base</b>		76"	192 cm	76"	192 cm
<b>Weight</b>	With batteries	436 lb	210 kg	463 lb	210 kg
	Without batteries	300 lb	136 kg	300 lb	136 kg
	Add for canopy	+ 26 lb	+ 12 kg	+ 26 lb	+ 12 kg
	Add for wide wheels			+ 3 kg	
<b>Weight capacity Inc. driver</b>		551 lb	250 kg	551 lb	250 kg
<b>Travel range</b>		33 m	50 km	33 m	50 km
<b>Maximum speed</b>		7.5 mph	12 Km/h	7.5 mph	12 Km/h
<b>Maximun climbing angle</b>		13%			
<b>Turning radius</b>		79"	200 cm	79"	200 cm
<b>Seating</b>		18"	46 cm	33"	85 cm
<b>Tire type</b>		Pneumatic			
<b>Tire size</b>	Front	3X10"			
	Rear	16X7.5-8.0"			
<b>Battery type</b>	Two	12V 150A/h			
<b>Power unit</b>	Rear wheel drive	24V DC motor   1400 W			
<b>Controller type</b>		SD 140 A			
<b>Charger type</b>		15A			
<b>Color</b>		Metallic Silver / Dark Grey			

Tested by manufacturer, based on actual parameters.